

TOUGH PHONE COMMUNICATION SYSTEM

REENTRANT HORNS
13651 & 13652



DESCRIPTION

Models 13651 and 13652 are exceptionally efficient reentrant horns, utilizing exponentially flared trumpets with 2 1/2 ft or 3 1/2 ft air columns respectively. They offer a combination of low distortion and high output, along with remarkable amplifier economy. A positively-locking, multi-angle bracket facilitates convenient mounting in any position. The horns are ideal for covering large open industrial areas.



FEATURES:

- Unique Adjustable Mounting Bracket
- Excellent Voice Frequencies
- Spun Aluminum with Gray Epoxy Finish
- Compatible with any 1 3/8 " threaded driver

SPECIFICATIONS	13651	13652
Low Frequency Roll off:		
-6 dB	500 Hz	300 Hz
-12 dB	420 Hz	200 Hz
Dispersion:		
1 kHz	82°	50°
2 kHz	42°	40°
4 kHz	37°	37°
Throat Diameter:	0.7"	0.7"
Air Column Length:	30"	42"
Dimensions (Diam x Depth):	16.3" x 12" (41.4 x 30.5 cm)	20.4 x 15.8 (51.8 x 40.1cm)
Shipping Weight:	8.25 lbs. (3.7 kg)	11.75 lbs. (5.3 kg)