



TOUGH PHONE COMMUNICATION SYSTEM

HAZARDOUS AREA
COMPRESSION DRIVERS

13600 & 13601

DESCRIPTION

Models 13600 and 13601 are both rated at 30 watts and are for use in medium power public address applications. "Rim centered" voice coils and phenolic diaphragms assure long life under extreme operating conditions.

A weatherproof rear housing provides quick connection using the sealed gland nut provided. Exterior parts are injection molded polycarbonate, and all metal parts are treated for resistance to fungus and high humidity. Model 13600 has an impedance rating of 8 ohm, Model 13601 is rated at 16 ohms. Both drivers are approved for use in Class I, Division 2, Groups A,B,C and D, Class II, Division 2, Group F and G areas. Use with 13651, 13652 or 13653 horns.



FEATURES:

- 30 Watts Power Handling
- Wide Frequency Response
- Low Distortion
- FM Approved for Division 2 Hazardous Area

SPECIFICATIONS	13600	13601
Frequency Response (Hz):	500 Hz - 4 k Hz \pm 5 dB	500 Hz - 4 k Hz \pm 5 dB
Power Handling: (500-5 K Hz Pink Noise)	30 Watts	30 Watts
Sensitivity: (1 Watt, 1 m, 500-5K Hz)	106 dB SPL	106 dB SPL
Nominal Impedance:	8 Ω	16 Ω
Color:	Gray	Gray
Inches (cm) Depth:	5.2 (13.2)	5.2 (13.2)
Dimensions Diameter:	4.2 (10.6)	4.2 (10.6)
Net Weight lb. (kg):	3.5 (1.6)	3.5 (1.6)